

Intrinsically Safe - Dust LIPS® SERIES E115		Part Number Coding								
		E115	Travel	A	I/L	Option 1	Option 2	Option 3	Option 4	Z000
Submersible Stand Alone Rugged Linear Position Sensor										
Travel										
mm of stroke	Value									
Electrical Interface Options										
Input	Output									
+ 5 V dc	See below	A								
Cable Gland										
Cable - Radial Gland IP68	Please specify cable length in cm.	Ixx								
Cable - Axial Gland IP68	Please specify cable length in cm.	Lxx	eg. L2000 specifies 20 metres of cable with an axial cable gland							
OPTIONS										
Body Fittings		Option 1								
M8 Rod Eye on Body	Only available with option I	N								
Body Clamps (1 pair)		P								
Body Clamps (2 pairs)		P2								
Spring Return		Option 2								
Up to 300mm stroke only										
Spring return to extended position		R								
Push Rod End Fitting		Option 3								
None - M5 female thread only	Standard option no code	Blank								
Dome End (for use with option R)		T								
M5 Rod Eye on Push Rod		U								
Non Captive Push Rod Tube		Option 4								
Push Rod not retained in body		V								
Tighter Linearity		Zsuffix								
± 0.1% Linearity		Z650								

Please Note: This sensor *must* be used with a Galvanic Isolation Amplifier - See X005 sheet for Output opti