

Intrinsically Safe - Dust LIPS® SERIES E118		Part Number Coding							
		E118	Travel	A	L/J	N	Option 1	Option 2	Option 3
<b>Short Stroke Slim-Line Position Sensor</b>									
<b>Travel</b>									
mm of stroke	Value								
<b>Electrical Interface Options</b>									
<b>Input</b>	<b>Output</b>								
+ 5 V dc	See below	A							
Adjusts not available									
<b>Cable / Connector</b>									
Cable - Axial Gland IP67	Please specify cable length in cm.	LXX	eg. L2000 specifies 20 metres of cable with an axial cable gland						
Connector - Axial M8 4 pin IP67		J							
<b>OPTIONS</b>									
<b>Housing</b>		Standard Fit							
Front Flange		N							
<b>Spring Return</b>		Option 1							
Spring Return		R							
<b>Plunger End Fitting</b>		Option 2							
Dome End		T							
<b>Plunger (Armature) Guide</b>		Option 3							
Free Plunger (no inner guide bearing)	Not available with option R or T	V							
<b>Tighter Linearity</b>		Zsuffix							
± 0.1% Linearity		Z650							

**Please Note: This sensor *must* be used with a Galvanic Isolation Amplifier - See X005 sheet for Output opti**