

Intrinsically Safe - Mining LIPS® SERIES M117		Part Number Coding									
		M117	Travel	A	Blank	Body & Cable	Option 1	Option 2	Option 3	Option 4	Z000
<b>Slim-line Linear Sensor</b>											
<b>Travel</b>											
mm of stroke	Value										
<b>Electrical Interface Options</b>											
<b>Input</b>	<b>Output</b>										
+ 5 V dc	See below	A									
<b>Adjusts not available</b>											
<b>Body Style</b>											
Connector - Axial		J									
Connector - Radial		K									
Cable - Axial Gland	Please specify cable length in cm.	Lxx									
<b>OPTIONS</b>											
<b>Body Fittings</b>		<b>Option 1</b>									
M5 Rod Eye fitted to body	Only available on Ixx Version	N									
<b>Body Clamp</b>		<b>Option 2</b>									
S/S Body Clamps (1 pair)		P									
<b>Push Rod Fittings</b>		<b>Option 3</b>									
M5 Rod Eye fitted to push rod		U									
<b>Non Captive Push Rod</b>		<b>Option 4</b>									
Push Rod not retained in body		V									
<b>Tighter Linearity</b>		<b>Zsuffix</b>									
± 0.1% Linearity		Z650									

**Please Note: This sensor *must* be used with a Galvanic Isolation Amplifier - See X005 sheet for Output options an**