

Part Number Coding

CYLINDER LIPS® P106			P106	Travel	Electrical Interface	Sealed Adjuster	Conn / Cable	N	Option 1	R	Option 2	Z code
Internally Mounted Cylinder Sensor												
Travel												
mm of stroke	Value											
Electrical Interface Options												
Input	Output											
+ 5V dc nom.± 0.5V	0.5 to 4.5V dc ratiometric	A										
24V dc nom. +9-28V	0.5-4.5V dc	G										
±15V dc nom. ±9-28V	±5V dc	B										
24V dc nom. +13-28V	0.5 to 9.5V dc	C										
± 15V dc nom. ±13.5-28V	±10 V dc	D										
24V dc nom. +18-28V	4 to 20mA (2 wire)	E										
24V dc nom. +13-28V	4 to 20mA (3 wire sink)	F										
24V dc nom. +13-28V	4 to 20mA (3 wire source)	H										
Calibration Adjusters												
Trim Pots Accessible	Blank											
Sealed Trim Pots	Y											
Connector / Cable												
Connector - Axial IP65	Hirschmann GD series	J										
Connector - Axial IP67	M12 - 4 pin	J + Z600										
(for sensors with Trim Pots sealed)												
Connector - Axial IP67	M12 - 4 pin	J + Z601										
(for sensors with Trim Pots Accessible)												
Cable - Axial Gland IP67	Please specify cable length in cm.	Lxx										
Cable - Axial Short Gland IP67	Please specify cable length in cm.	Mxx										
eg. L2000 specifies 20 metres of cable with an axial cable gland												
Note: restricted cable pull strength												
OPTIONS												
Internal Housing Size												
20 mm Diameter	Standard Fit	N										
Standard Fit												
Electronics Housing												
Flanged	T											
M18 Thread	P											
Option 1												
Target Tube												
Stainless Steel 7.7 mm	Standard Fit	R										
Aluminium 7.0 mm	S											
Standard Fit												
Flange Style and Position												
Please select one.												
None	U											
P&G	Vxx											
Tempo	Wxx											
PH	Xxx											
See Drawing TG24-11 for flange details												
Tighter Linearity												
± 0.1% Linearity	upto 400mm stroke only	Z650										
Zsuffix												