

RIPS® SERIES P502				Part Number Coding					
				P502	Travel	Electrical Interface	Sealed Adjuster	Conn / Cable	Option 1
<b>Small Angle Industrial Rotary Sensor</b>									
<b>Travel</b>									
degrees rotation	5° to 15°	Value							
<b>Electrical Interface Options</b>									
Input	Output								
+ 5V dc nom. ± 0.5V	0.5 to 4.5V dc ratiometric	A							
24V dc nom. +9-28V	0.5-4.5V dc	G							
±15V dc nom. ±9-28V	±5V dc	B							
24V dc nom. +13-28V	0.5 to 9.5V dc	C							
± 15V dc nom. ±13.5-28V	±10 V dc	D							
24V dc nom. +18-28V	4 to 20mA (2 wire)	E							
24V dc nom. +13-28V	4 to 20mA (3 wire sink)	F							
24V dc nom. +13-28V	4 to 20mA (3 wire source)	H							
<b>Calibration Adjusters</b>									
Trim Pots Accessible		Blank							
Sealed Trim Pots		Y							
<b>Connector / Cable</b>									
Connector - Axial IP65	Hirschmann GD series	J							
Connector - Axial IP67	M12 - 4 pin	J + Z600							
	(for sensors with Trim Pots sealed)								
Connector - Axial IP67	M12 - 4 pin	J + Z601							
	(for sensors with Trim Pots Accessible)								
Cable - Axial Gland IP67	Please specify cable length in cm.	Lxx							
Cable - Axial Short Gland IP67	Please specify cable length in cm.	Mxx							
<b>OPTIONS</b>									
<b>Spring Return</b>									
Fitted		N							
<b>Housing</b>									
Flanged	Standard option no code	Blank							
Servo Mount		P							